



OWNER'S MANUAL

Model MH1940

- **Important Safety Instructions**
- **Assembly Instructions**
- **Parts and Hardware Identification**



Tricam International
7677 Equitable Drive
Minneapolis, MN 55344
www.black-cat-products.com
800-304-1316

Platform Hand Truck

CAUTION:

Read, understand and follow ALL instructions before using this product

IMPORTANT SAFETY INSTRUCTIONS

1. **READ ALL INSTRUCTIONS CAREFULLY BEFORE USE.** If you do not understand these instructions, need clarification or further explanation, please call our toll free answer line for assistance at **1-800-304-1316** Monday through Friday 8:00 a.m. until 5:00 p.m. CST.
2. Do not load Folding Platform Cart with more than 330 lbs.
3. Do not allow children to use unsupervised. This Folding Platform Cart is not a toy.
4. Always distribute payload evenly.
5. If any parts become damaged, broken or misplaced, do not use the Folding Platform Cart until replacement parts can be obtained.
6. Do not operate or use on objects that can cause damage to the tires.
7. **SAVE THESE INSTRUCTIONS.**

ASSEMBLY INSTRUCTIONS

Your Folding Platform Cart requires assembly. Account for all parts and hardware before beginning assembly. If any parts are missing, damaged, or if you have questions or need additional instructions, **DO NOT RETURN THIS PRODUCT TO THE RETAILER**, call the manufacturer at **1-800-304-1316**.

Tools required for assembly: 12 mm wrench or 12 mm socket driver

Refer to the exploded drawing and the parts list below during assembly.

STEP 1: Position handle on top of platform so that the bolt holes line up.

STEP 2: Place the fixed casters nearest to the end of the platform with the handle and align holes. Insert the (4) 45 mm bolts thru the caster and platform up thru the handle assembly holes. Attach with washers, lock washers and nuts. Flip cart over and attach remaining (4) 25 mm bolts into the remaining fixed caster holes and platform.

STEP 3: Place the swivel casters nearest to the end of the platform without the handle. Attach the swivel casters using the (8) 25 mm bolts and lock washers included.

STEP 4: To open the handle into the operating position, lift on the handle until the handle locks into place. To close the handle, simply step down on the metal bar located at the base of the handle and fold the handle down to the storing position.

PARTS AND HARDWARE IDENTIFICATION

- 1 Platform - (1)
- 2 Handle Assembly - (1)
- 3 Swivel Casters - (2)
- 4 Fixed Casters - (2)
- 5 25 mm Bolts - (12)
- 6 45 mm Bolts - (4)
- 7 Lock Washers - (16)
- 8 Washers - (4)
- 9 Nuts - (4)

