



# OWNER'S MANUAL

Model MH1950



- Important Safety Instructions
- Assembly Instructions
- Parts and Hardware Identification

# Push Cart

## **CAUTION:**

Read, understand and follow ALL instructions before using this product

**Tricam International**  
**7677 Equitable Drive**  
**Minneapolis, MN 55344**  
**[www.black-cat-products.com](http://www.black-cat-products.com)**  
**800-304-1316**

Rev. 06/04

# IMPORTANT SAFETY INSTRUCTIONS

1. **READ ALL INSTRUCTIONS CAREFULLY BEFORE USE.** If you do not understand these instructions, need clarification or further explanation, please call our toll free answer line for assistance at **1-800-304-1316** Monday through Friday 8:00 a.m. until 5:00 p.m. CST.
2. Do not load Push Cart with more than 1000 lbs (450 kg).
3. Do not allow children to use the cart unsupervised. This Push Cart is not a toy.
4. Always distribute payload evenly over surface of deck.
5. If any parts become damaged, broken or misplaced do not use the cart until replacement parts can be obtained.
6. Do not operate or use on objects that can cause damage to the pneumatic tires or tubes.  
**Do not inflate tires more than 30 psi.**
7. **SAVE THESE INSTRUCTIONS.**

## ASSEMBLY INSTRUCTIONS

Your Push Cart requires assembly. Account for all parts and hardware before beginning assembly. If any parts are missing, damaged or if you have questions or need additional instructions **DO NOT RETURN THIS PRODUCT TO THE RETAILER**, call the manufacturer at **1-800-304-1316**.

Refer to the exploded drawing and the parts list on the following pages during assembly.

**STEP 1** Turn the cart bed upside down. Install the 80mm bolt to the anchor point behind the front axle assembly.

**STEP 2** Install the WHEELS in the following order.

- A. Place the wheel washer onto the axle.
- B. Place the Wheel onto the axle with the valve stem facing out.
- C. Use the wheel washer and then the cotter pin to secure the wheel.

**STEP 3** Turn the cart upright onto its wheels. Attach the handle using the 8 x 47mm handle bolts, washers, lock washers, and nuts.

## PARTS AND HARDWARE IDENTIFICATION

### To assemble handle to the yoke

- 1) 8 x 47mm bolts - (2)
- 2) Washers - (2)
- 3) Lock washers - (2)
- 4) Nuts - (2)

### To assemble the wheels

- 5) Big washers - (8)
- 6) Cotter pins - (4)

### Steering bolt assembly

- 7) 8 x 80mm bolt - (1)

### Parts List

- 8) Frame assembly - (1)
- 9) Handle - (1)
- 10) Wheel - (4)

